



## PRODUCT INFORMATION



270 North Road, Yate  
South Gloucester BS37 7LQ  
[www.action-products.co.uk](http://www.action-products.co.uk)

Tel: 01454-228702  
Fax: 01454-228703  
[sales@action-products.co.uk](mailto:sales@action-products.co.uk)

**DESIGNED TO BE KIND**

Professional Chemical Products  
**PROFESSIONAL GRADE  
TEX REMOVER**

(Interior Textured Plaster Based Coating Remover)  
EU Patent 0988348 US Patent 6635608

### ABOUT THE PRODUCT

#### PROFESSIONAL GRADE TEX REMOVER

Is a water-based gel, designed to be applied with a brush or via a Graco type sprayer. Easy to use, it makes light work of removing painted \*Artex.

#### VERSATILITY - PROFESSIONAL GRADE TEX REMOVER

Soaks through and softens emulsion and vinyl silk paint and \*Artex type interior textured coatings ready for easy removal.

#### SPEED + EFFICIENCY

- Faster than - sanding off
- Faster than - steaming off
- Faster than - re-plastering
- Easy to apply - suitable for large or small areas

#### ECONOMY More cost effective than

- Manual dry removal
- Hiring a steamer to remove textured coating
- Plastering over

#### SAFETY

- Non-corrosive
- Non-harmful to handle
- No dangerous vapours

#### USER FRIENDLINESS

Safe to use. Non-toxic. Easy to wash tools after use.

#### ENVIRONMENTAL FRIENDLINESS

This water-based formulation contains biodegradable, non-caustic, non-corrosive, neutral ingredients.



Made in the United Kingdom



**BFiY Winner 2002**



## PRODUCT INFORMATION



### WHERE TO USE

**Professional Grade Tex Remover** is a thick gel with excellent non-drip characteristics. Use it to remove interior Artex\* type coatings and emulsion and/or vinyl silk paint from ceilings and walls.

### WHAT IT DOES

**Professional Grade Tex Remover** is a water based formula which soaks into emulsion paint, vinyl silk paint and Artex\* type textured coatings on interior surfaces, softening them so that they can be easily scraped away.

### COVERAGE

1 litre covers from 2-4 square metres.  
5 litres covers upto 20 square metres.  
25 litres covers upto 100 square metres.

### HOW TO GET THE BEST RESULTS

1. Protect all areas not to be stripped, including textiles, polished wood surfaces and gloss paint from drips or spillages.
2. Apply **Professional Grade Tex Remover** generously with paintbrush or sprayer. DO NOT BRUSH OUT.
3. Where painted, allow to soak for 30 to 40 minutes (50-60 minutes for ready mixed Artex\*). Check a small area with a scraper. DO NOT ALLOW TO DRY OUT. Reactivate with warm water if drying occurs.
4. Remove wet softened coating with a scraper.
5. Apply a further generous coat of **Professional Grade Tex Remover** with a paintbrush or sprayer.
6. Allow to soak for 15 to 20 minutes (50-60 minutes for ready mixed Artex\*). Check a small area with a scraper. DO NOT ALLOW TO DRY OUT.
7. Remove wet softened coating with a scraper, taking care not to damage underlying surface.
8. Should any coating remain - repeat the process.
9. Wash down with water, using a cloth or sponge.
10. Ensure no trace of remover remains.
11. Allow to dry before redecorating.
12. Wash hands after use.

### NOTE

Some textured coatings may smell unpleasant when disturbed, but do not generally give off dangerous vapours. Ensure adequate ventilation.

### CAUTION

Wear protective goggles when working overhead. Where butyl rubber gloves to remove softened coating. When textured material contains asbestos, relevant regulations apply. Prolonged contact with **PROFESSIONAL GRADE TEX REMOVER** will remove gloss paint.

### STORAGE

Keep container securely closed. Store out of sunlight. Protect from frost.

### DISPOSAL OF WASTE

Please note that unless you are certain that the coating removed was manufactured after 1985, the waste should be treated as asbestos waste. If paint removed contained lead, then the waste material will contain lead. Dispose in accordance with regulations.

\* Artex is the trademark of BPB UK Limited